

ZEXA
28 Strathmore Road
New South Wales 2281 Australia
Telephone 02 4970 7708

Email sales@zexa.com.au
ABN Number: 56 117 205 375

Disclaimer:

ZEXA provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Product: PLATINUM MACHINE WASH

HAZARDOUS according to Safe Work Australia

DANGEROUS GOODS according to the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail

SIGNAL WORD/S



**DANGER
CORROSIVE**

 **Emergency Response No: 1800 039 008**

RECOMMENDED PPE



Health hazards

H302/312

H314

H318

Harmful if swallowed or in contact with skin
Causes severe skin burns and eye damage.
Causes serious eye damage

**1 IDENTIFICATION****IDENTIFICATION**

Product Code: ZPW
 Product Name: PLATINUM MACHINE WASH
 Other Names: Not applicable
 Product Use: Automatic machine dishwashing liquid
 Restrictions on use: Use according to Directions; Use appropriate PPE. Protect skin and eyes, use through dispenser provided

COMPANY DETAILS

Company: ZEXA
 ABN Number: 56 117 205 375
 Address: 28 Strathmore Road
 CAVES BEACH NSW 2281
 Telephone Number: (02) 4970 7708
 Emergency Telephone Number: CHEMWATCH 1800 039 008

Other Information: This information summarises our best knowledge on the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products.

2 HAZARD IDENTIFICATION

HAZARDOUS SUBSTANCE according to criteria of Safe Work Australia
DANGEROUS GOODS as classified by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

Classification of the substance or mixture:

Acute Toxicity - Category 4
 Corrosive to Metals - Category 1
 Skin Corrosion - Sub-Category 1A
 Eye Damage - Category 1

SIGNALWORD/S:

DANGER
CORROSIVE



Corrosion

Hazard Statements**Physical hazards**

H290 May be corrosive to metals.

Health hazards

H302/312 Harmful if swallowed or in contact with skin
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage

Environmental hazards

H402 Harmful to aquatic life

Other Hazards

Not Listed

Precautionary statements**General precautionary statements****Prevention precautionary statements**

P260 Do not breathe mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response precautionary statements



P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363 Wash contaminated clothing before re-use.
P310 Immediately call a POISON CENTER or doctor/physician.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P390 Absorb spillage to prevent material damage.

Storage precautionary statements

P405 Store locked up.
P406 Store in corrosive resistant container with a resistant inner liner.

Disposal precautionary statements

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Poisons Schedule (SUSMP): S6 Poison.

3 COMPOSITION

Ingredients

Chemical Entity	CAS Number	Proportion	Risk Phrases
POTASSIUM HYDROXIDE	[1310-58-3]	10 - 30%	H290 H314 H318
DISODIUM METASILICATE	[10213-79-3]	1 – 10%	H302/312 H314 H318
Water	[7732-18-5]	> 60%	
Ingredients determined not to be hazardous		Balance	

4 FIRST AID MEASURES

Ingestion: If swallowed do NOT induce vomiting. Immediately wash out mouth with water. Seek urgent medical attention.
Eye: If in eyes, hold eye lids apart and flush eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a doctor, or for at least 15 minutes. Seek urgent medical attention.
Skin: If skin contact occurs, remove contaminated clothing and flush skin and hair with running water. Do not re-use contaminated clothing until washed. Seek medical attention.
Inhaled: Remove from contaminated area to fresh air. If problem persists seek urgent medical attention
First Aid Facilities Eye wash and safety shower
Advice to Doctor Treat symptomatically, Can cause severe eye damage.

5 FIRE FIGHTING MEASURES

Fire Extinguishing Media: Use appropriate extinguishing media to suit surrounding area
Hazards from Combustion: Material does not burn
Precaution for Fire Fighters: Wear chemical splash suit and SCBA
Corrosive liquid. Contact with metals may evolve flammable hydrogen gas
Hazchem 2R

6 ACCIDENTAL RELEASE MEASURES

Emergency Procedures Keep unauthorised people away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing
Clean Up Spills will be slippery so treat promptly. For minor spills mop up and rinse with water. For larger spills absorb material on mineral absorbent material or absorbent pads. Collect and put into plastic bags and dispose of through waste disposal contractor. Rinse area with water.

7 HANDLING AND STORAGE

Handling Wear appropriate protective clothing to prevent skin and eye contact. Use in well ventilated area. Keep containers closed when not in use. Maintain a high standard of personal hygiene. Wash hands immediately after using product



Storage Corrosive product. Store in cool, dry, well ventilated place out of direct sunlight. Store in closed containers. Store away from incompatible materials such as acids, aluminium and zinc. Ensure storage area is secure

8 EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Standards None listed for product. However exposure standards for potassium hydroxide [NOHSC: 1008(2004)] are:

Potassium Hydroxide: TWA 2mg/m³ Peak limitation

Engineering Controls Do not inhale vapours. Use in well ventilated area and maintain levels below exposure standards.

Personal Protective Equipment Wear chemical goggles or safety glasses and impervious gloves when using product;. Use through the electronic dispensing equipment. Be sure that the equipment is functioning correctly , and use care when servicing the equipment

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

RECOMENDED



CHEMICAL GOGGLES or SAFETY GLASSES
IMPERVIOUS GLOVES
FACE SHIELD

Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If risk of inhalation exists, wear suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear red coloured liquid	
Formula	Not applicable.	
Odour	Odourless	
Vapour Pressure	Not applicable.	
Vapour Density	Not determined	
Boiling Point	> 100 °C	
Melting Point	Not applicable. C	
Solubility in Water	Soluble at use dilutions	
Specific Gravity	1.2 (Water = 1)	
Flash Point	Not applicable.	
pH	>13.0 (1% solution)	
Lower Explosion Limit	Not applicable.	
Upper Explosion Limit	Not applicable.	
Ignition Temperature	Not applicable.	
Specific Heat Value	Not applicable.	
Particle Size	Not applicable.	
Volatile Organic Compounds (VOC) Content	Not applicable.	
Evaporation Rate	Not applicable.	
Viscosity	Not applicable.	
Percent Volatile	>60%	
Octanol/Water partition coefficient		Not applicable.
Saturated Vapour Concentration		Not applicable.
Additional Characteristics		Not applicable.
Flame Propagation/Burning Rate of Solid Materials		Not applicable.
Properties of Materials That May Initiate or Contribute to Fire Intensity		Not applicable.
Potential for Dust Explosion		Not applicable.
Reactions that Release Flammable Gases	Contact with reactive metals may evolve highly flammable hydrogen gas	
Fast of Intensely Burning Characteristics		Not applicable.
Non-flammables That Could Contribute Unusual Hazards to a Fire		Not applicable.
Release of Invisible Flammable Vapours and Gases		Not applicable.
Decomposition Temperature		Not determined
Additional Information		

**10 STABILITY AND REACTIVITY**

Stability	Stable under normal conditions of use and storage.
Hazardous Decomposition Products:	May emit heat when mixed with acids.
Hazardous Polymerization:	Will not occur.
Incompatibilities:	Incompatible with acids, oxidising agents (i.e. peroxides), active metals and heat.
Conditions to Avoid:	Incompatible with acids, oxidising agents (i.e. peroxides), active metals aluminium, tin and zinc

11 TOXICOLOGICAL INFORMATION

Ingestion	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and bleeding. Can cause chemical burns to the mouth, oesophagus and gastrointestinal tract
Eye	Corrosive to eyes. Will cause severe irritation and chemical burns. Contamination of eyes can result in permanent injury or blindness
Skin	Contact with skin will result in severe irritation. Corrosive to skin – may cause skin burns
Inhalation	Mist generated may cause severe irritation to the mucous membranes and upper respiratory tract
Toxicological Data	Non available for PLATINUM MACHINE WASH.

12 ECOLOGICAL INFORMATION

Ecotoxicity	No data available.
Persistence and Degradability	Does not cause biological oxygen deficit. Methods for determination of biodegradability can not be applied to inorganic substances.
Mobility	Fully soluble in water.
Environmental Fate (Exposure)	Do NOT let product reach waterways, drains and sewers.
Bioaccumulative Potential	No information available on bioaccumulation for this product.

13 DISPOSAL CONSIDERATIONS

Disposal	Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Dispose of in accordance with all local, state and federal regulations. All empty packaging should be disposed of in accordance with Local, State, and Federal Regulations or recycled/reconditioned at an approved facility.
Special Precautions for Land Fill or Incineration	Contact a specialist disposal company or the local waste regulator for advice. This should be done in accordance with 'The Hazardous Waste Act'.

14 TRANSPORT INFORMATION**Road and Rail Transport**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN No:	1719
Transport Hazard Class:	8 Corrosive
Packing Group:	III
Proper Shipping Name:	CAUSTIC ALKALI LIQUID N.O.S. (Contains Potassium hydroxide)
Hazchem or Emergency Action Code:	2R

**Marine Transport**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No:	1719
Transport Hazard Class:	8 Corrosive
Packing Group:	III
Proper Shipping Name or Technical Name:	CAUSTIC ALKALI LIQUID N.O.S. (Contains Potassium hydroxide)



IMDG EMS Fire:	F-A
IMDG EMS Spill:	S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No:	1719
Transport Hazard Class:	8 Corrosive
Packing Group:	III
Proper Shipping Name or Technical Name:	CAUSTIC ALKALI LIQUID N.O.S. (Contains Potassium hydroxide)



15 REGULATORY INFORMATION

Poisons Schedule S6
EPG 8A1
AICS Name Potassium hydroxide in water Mixture

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

And a Dangerous Good according to ADG Code

Classification of the substance or mixture:

Corrosive to Metals - Category 1
 Acute Toxicity - Category 4
 Corrosive to Metals - Category 1
 Skin Corrosion - Sub-Category 1A
 Eye Damage - Category 1

Hazard Statement(s):

H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage

16 OTHER INFORMATION

Literature References No data available.
Sources for Data No data available.

Legend to Abbreviations and Acronyms

< less than
 > greater than
AICS Australian Inventory of Chemical Substances
CAS Chemical Abstracts Service (Registry Number)
cm² square centimetres
CO₂ Carbon Dioxide
COD Chemical Oxygen Demand
deg C (°C) degrees Celsius
ERMA Environmental Risk Management Authority
G gram
g/cm³ grams per cubic centimetre
g/l grams per litre
LD50 LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals
Ltr Litre
m³ cubic metre
mbar millibar
mg milligram
mg/24H milligrams per 24 hours
mg/kg milligrams per kilogram
mg/m³ milligrams per cubic metre
Misc miscible
Miscible liquids form one homogeneous liquid phase regardless of the amount of either component present
mm millimetre
mPa.s milli Pascal per second

HSNO Hazardous Substance and New Organism
IDLH Immediately Dangerous to Life and Health
Immiscible liquids are insoluble in each other
Kg kilogram
kg/m³ kilograms per cubic metre
LC50 LC stands for lethal concentration. LC50 is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours.
N/A Not Applicable
NOHSC National Occupational Health and Safety Commission
OECD Organization for Economic Co-operation and Development
PEL Permissible Exposure Limit
ppb parts per billion
ppm parts per million
ppm/2h parts per million per 2 hours
ppm/6h parts per million per 6 hours
RCP Reciprocal Calculation Procedure
STEL Short Term Exposure Limit
TLV Threshold Limit Value
tne tonne
TWA Time Weighted Average
ug/24H micrograms per 24 hours
UN United Nations (number)
Wt weight

Date Prepared: Thursday 9th February 2017
 New SDS

Version: 1 Supersedes:

ZEXA
 28 Strathmore Road
 CAVES BEACH NSW 2281

Telephone: (02) 4970 7708
 e-Mail: sales@zexa.com.au